



Only great ideas need to stick.

i-gum®

A comfortable self contained backpack is worn by the user allowing for complete freedom of movement and easy usability. The unit is attached to an ergonomic lance designed specifically to ensure fast, reliable and easy operation with maximum chewing gum removal. At the point of contact, our specially designed brush emits a pH neutral and safe enzyme steam mixture to dissolving the chewing gum, which can then be brushed away. Beside the comfortable harness you also have the option to wheel it!





6 seconds is all it takes

The i-gum apparatus needs only 6 seconds to eliminate any unwanted sticky materials (chewing gum/stickers/lining glue). Increase your efficiency and start cutting down on waiting hours.

No water or power supply

To operate the machine, just point the lance to the area or stains that need to be cleaned and watch the i-gum perform its magic.

No matter which surface

Hardwood, soft floors, tarmac, doors, cabinets, plywood, concrete or steel. The i-gum operates at maximum capacity, and removes sticky residue anywhere and everywhere.

Centralized controls

Centralized controls are located in the head of the machine. All of your actions, switches and controls are within the reach of your fingertips.

Safe to touch

Designed to be user-friendly and to work in different environments, there are no hazardous or dangerous fumes or heat present when working with the i-gum.

“When the dust settles on an outdoor event, removing the gum residue is one of the hardest parts of the clean-up. But thanks to the i-gum, our team can clean up the location in just a single day. Perfect!”

Voltage

230 V
240 V
115 V
110 V

Art code

IGM.I-V. 1110C
IGM.I-V.1210C
IGM.I-V.2510C
IGM.I-V. 4610C

TECHNICAL SPECIFICATIONS

Weight of product	12.8 Kg
Weight In box <i>incl. fluidx4 gasx2</i>	25 Kg
Size body	36 x 30 x 57
Size with lance	36 x 30 x 113
Size box L*W*H	120 X 35 X 40 cm
Ignition battery spec. Li-ion	14.8 V 6.6 Ah 95.04 Wh
Power (Watt) of Fan	DC 12 V 4 W
Material	LLDPE, ABS, PC, PP, Aluminum
Gas Capacity	2.6 Kg/H
Tank Capacity	2.5 Ltr
CBM	0,168
20' Container loading quality	145
Warranty	1 year

