

## Limescale remover RM 101 ASF



Hydrochloric acid basis for fast descaling. Quickly removes the most stubborn deposits of limescale and detergent and offers long-lasting protection against corrosion. Particularly suitable for heater coils in high-pressure cleaners.



NTA-free



### Properties

- Service product for decalcification of the heating coil
- Reliably removes stubborn calcification
- Effective quickly
- Rapidly separates oil/water in the oil separator (easy to separate=asf)
- NTA free

### Areas:

Machine protector:

Machine maintenance, decalcification of hot water systems.

### Application

- High-pressure washers

Part number

5 l

6.295-398.0

pH



**Application:****High-pressure washers**

- Combine the product with the appropriate dosage and fresh water.
- Set the temperature on the device.
- 1-40°C processing temperature.
- Vacuum the solution through a water connection and drive in a circuit (with the hand spraygun screwed off).
- Reaction time 10-15 minutes, depending on the degree of soiling.
- Rinse the device with water and then neutralise with an alkaline cleaning agent.

**Directions for use:**

- Only descale in a circuit.
- Ensure good ventilation.
- Observe safety measures for corrosive fluids.

**Further information:**

- Material Safety Data Sheet (MSDS)

**Dosage and yield:**

Content:	Cleaning method:	Primary mixture:	Dosage:	Contamination:	Productivity:
1000 ml			10 %	heavy	1 Heizschlange

Please contact us for more information:

**Kärcher UK Ltd**

Kärcher House  
Brookhill Way  
Banbury  
Oxon OX16 3ED